



**ENGINEERED-TO-ORDER
FORKLIFT-FREE MATERIAL HANDLING SOLUTIONS**



Model PC 300

Shown with optional
headlight



Standard Features

- Dual Front Wheels
- Programmable Characteristics
- Sealed 350 Amp Controller
- Tamper-proof Speed Control
- Regenerative Braking
- Electronic Throttle Control
- On-board Diagnostics
- Maintenance Management System
- Contactor-less Drive System
- Sealed Direct Drive Transaxle
- Sealed On-board Automatic Charger
- Battery Discharge Indicator
- LCD Hour Meter
- Genuine 14 Gauge Diamond Plate Steel Chassis
- Parking Brake

We build custom vehicles, too!

WESLEY INTERNATIONAL

3680 Chestnut Street
Scottsdale, GA 30079
Toll Free (800) 241-2869
Phone (404) 292-7441
Fax (404) 292-8469
www.wesleyinternational.com

**PERSONNEL CARRIER
PC 300 SERIES**

Industrial environments demand a special kind of equipment. That's why Wesley International's electric vehicles are meticulously engineered for safety, reliability and low maintenance. From the dual front wheels to the sealed motor, Wesley's vehicles offer increased stability and reduced down time. As a result, our Pack Mule® has been the choice of discerning buyers for years. They know that increased productivity and reduced maintenance costs deliver greater profit.

Our Pack Mule PC 300 is a two-passenger vehicle that is perfect for manufacturing facilities, airports, warehouses, parts distribution centers, greenhouses and more. If our standard size doesn't fit your needs, we will custom build a vehicle that is just right for you. Our custom equipment is made with the same commitment to quality, safety and reliability.

Why buy a Pack Mule? Unique safety features, increased productivity, reduced maintenance and custom design...Can you afford not to buy a Pack Mule?

Vehicles shown
with optional
headlight



MODEL PC 300



MODEL PC 325



PERSONNEL CARRIER PC 300 SERIES

SPECIFICATIONS	PC 300	PC 325
Maximum Personnel	2	1
DIMENSIONS		
Length	86.5 in. (219.7 cm)	74.5 in. (189.2 cm)
Width	32 in. (81.3 cm)	32 in. (81.3 cm)
Height	39 in. (99.1 cm)	39 in. (99.1 cm)
Wheel Base	53.5 in. (135.9 cm)	53.5 in. (135.9 cm)
Ground Clearance	3 in. (7.6 cm)	3 in. (7.6 cm)
Deck Height	24 in. (61 cm)	24 in. (61 cm)
Deck Size	31.5 in. (80 cm) x 19.5 in. (49.5 cm)	31.5 in. (80 cm) x 19.5 in. (49.5 cm)
Turning Radius	92 in. (233.7 cm)	82 in. (208.3 cm)
CAPACITIES*		
Load Capacity	750 lb. (340.2 kg)	750 lb. (340.2 kg)
Towing Capacity	Not Applicable	2000 lb. (907 kg)
WHEELS & TIRES		
Wheels	4	4
Tires Pneumatic	4.80 x 8 LR B	4.80 x 8 LR B
ELECTRICAL		
Battery Type	220 amp hour	220 amp hour
System Voltage (Battery Quantity)	24 volt (4-6 volt) 36 volt (6-6 volt) 48 volt (6-8 volt)	24 volt (4-6 volt) 36 volt (6-6 volt) 48 volt (6-8 volt)
Sealed Motor (separately excited)	5 hp / 7.5 hp / 10 hp	5 hp / 7.5 hp / 10 hp
Sealed Programmable Controller	350 amp	350 amp
Automatic Built-in Charger	25 amp, 115 volt, 60 hz	25 amp, 115 volt, 60 hz
Instrumentation	LED Battery Discharge LCD Hour Meter	LED Battery Discharge LCD Hour Meter
Removable Key Switch	3-Position Safety Key	3-Position Safety Key
Horn	Foot-operated Push Button	Foot Operated Push Button
TRANSAXLE & TRANSMISSION		
Sealed Drive Axle	Heavy-duty Direct Drive Helical Gear	Heavy-duty Direct Drive Helical Gear
Transmission Ratio	12.44:1	12.44:1
Programmable Maximum Speed	8 mph 11 mph 14 mph	8 mph 11 mph 14 mph
STEERING, BRAKES & SUSPENSION		
Steering	Tiller Steering	
Service Brakes	Self-adjusting Wheel Drum Brakes	
Electronic Brakes	Programmable Electronic Regenerative Braking	
Park Brake	Pedal-Style Parking Brake	

Optional Equipment

- Perma-Key Switch
- Removable Battery System
- Battery Cart with Charger
- 245 Amp Hour Batteries
- Ergonomic Anti-Fatigue Mat
- Diagnostic Handset
- Headlight / Taillight
- Back-up Alarm
- Proximity Alarm
- Flashing Safety Beacon
- Rubber Deck Cover
- Foam-filled Tires
- Non-marking Tires
- Dura Solid Tires
- Galvanized Frame
- Various Hitches

Specifications subject to change
without notice.

Wesley International electric vehicles
are designed to conform with ANSI
B56.8 and OSHA standards.

* Not to be combined. Can carry load or tow.

DISTRIBUTED BY: