



**ENGINEERED-TO-ORDER  
FORKLIFT-FREE MATERIAL HANDLING SOLUTIONS**



Model PMT 4500

Shown with optional  
headlight and removable  
battery system



**Standard Features**

- Dual Front Wheels
- Programmable Characteristics
- Sealed 350 Amp Controller
- Tamper-proof Speed Control
- Regenerative Braking
- Electronic Throttle Control
- On-board Diagnostics
- Maintenance Management System
- Contactor-less Drive System
- Sealed Direct Drive Transaxle
- Sealed On-board Automatic Charger
- Battery Discharge Indicator
- LCD Hour Meter
- Genuine 14 Gauge Diamond Plate Steel Chassis
- Parking Brake

**We build custom vehicles, too!**

**WESLEY INTERNATIONAL**

3680 Chestnut Street  
Scottdale, GA 30079  
Toll Free (800) 241-2869  
Phone (404) 292-7441  
Fax (404) 292-8469  
www.wesleyinternational.com

**TOW VEHICLES  
PMT SERIES**

Industrial environments demand a special kind of equipment. That's why Wesley International's electric vehicles are meticulously engineered for safety, reliability and low maintenance. From the dual front wheels to the sealed motor, Wesley's stock chasers offer increased stability and reduced down time. As a result, our Power Mule™ stock chasers have been the choice of discerning buyers for years. They know that increased productivity and reduced maintenance costs deliver greater profit.

The Power Mule PMT series tow vehicles can tow up to 5,000 lbs. They are perfect for manufacturing facilities, airports, warehouses, parts distribution centers, greenhouses and more. If our standard size doesn't fit your needs, we will custom build a vehicle that is just right for you. Our custom equipment is made with the same commitment to quality, safety and reliability.

Why buy a Power Mule? Unique safety features, increased productivity, reduced maintenance and custom design...Can you afford not to buy a Power Mule?

Shown with optional  
headlight and removable  
battery system



PMT 4500  
TOW VEHICLE



PMT 5000  
TOW VEHICLE



## TOW VEHICLES PMT SERIES

SPECIFICATIONS	PMT 4500	PMT 5000
Maximum Personnel	2 / seated	1 / standing
<b>DIMENSIONS</b>		
Length	86.5 in. (219.4 cm)	60 in. (152.4 cm)
Width	36 in. (91.4 cm)	37.25 in. (94.7 cm)
Height	45 in. (114.3 cm)	50.5 in. (128.3 cm)
Wheel Base	65.5 in. (116.4 cm)	42.25 in. (107.3 cm)
Ground Clearance	3 in. (7.6 cm)	3 in. (7.6 cm)
Deck Height	23.5 in. (59.7 cm)	35 in. (88.9 cm)
Deck Size	35.5 in. (90.2 cm) x 30.75 in. (78.2 cm)	20.25 in. (51.4 cm) x 37 in. (93.9 cm)
Turning Radius	92 in. (233.7 cm)	70 in. (177.8 cm)
<b>CAPACITIES*</b>		
Load Capacity	1000 lb. (453.6 kg)	1000 lb. (453.6 kg)
Towing Capacity	5000 lb. (2268 kg)	5000 lb. (907 kg)
<b>WHEELS &amp; TIRES</b>		
Wheels	4	4
Tires Pneumatic	Front 165/65/8 Rear 205/50/10	Front 165/65/8 Rear 205/50/10
<b>ELECTRICAL</b>		
Battery Type	220 amp hour	220 amp hour
System Voltage (Battery Quantity)	36 volt (6-6 volt) 48 volt (8-6 volt)	36 volt (6-6 volt) 48 volt (8-6 volt)
Sealed Motor (separately excited)	7.5 hp / 10 hp	7.5 hp / 10 hp
Sealed Programmable Controller	350 amp	350 amp
Automatic Built-in Charger	25 amp, 115 volt, 60 hz	25 amp, 115 volt, 60 hz
Instrumentation	LED Battery Discharge LCD Hour Meter	LED Battery Discharge LCD Hour Meter
Removable Key Switch	3-Position Safety Key	3-Position Safety Key
Horn	Push Button on Console	Push Button on Console
<b>TRANSAXLE &amp; TRANSMISSION</b>		
Sealed Drive Axle	Heavy-duty Direct Drive Helical Gear	Heavy-duty Direct Drive Helical Gear
Transmission Ratio	17.00:1	17.00:1
Programmable Maximum Speed	8 mph / 11 mph	8 mph / 11 mph
<b>STEERING, BRAKES &amp; SUSPENSION</b>		
Steering	3-Spoke Contour Wheel	
Service Brakes	Self-adjusting Wheel Drum Brakes	
Electronic Brakes	Programmable Electronic Regenerative Braking	
Park Brake	Automatic Deadman Parking Brake	

\* Not to be combined. Can carry load or tow.

### Optional Equipment

- Perma-Key Switch
- Removable Battery System
- Battery Cart with Charger
- 245 Amp Hour Batteries
- Ergonomic Anti-Fatigue Mat
- Diagnostic Handset
- Extended Deck Lengths
- Headlight / Taillight
- Back-up Alarm
- Proximity Alarm
- Flashing Safety Beacon
- Rubber Deck Cover
- Small / Large Clipboard
- Foam-filled Tires
- Non-marking Tires
- Dura Solid Tires
- Various hitches
- 5 or 6-Step Ladder (87" or 95")

Specifications subject to change without notice.

Wesley International electric vehicles are designed to conform with ANSI B56.8 and OSHA standards.

**DISTRIBUTED BY:**